


ANTIQUE RELEASE - 35# PL AUTUMN BROWN

Version 3.0

Print Date 04/25/2013

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : ANTIQUE RELEASE - 35# PL AUTUMN BROWN
 PL AUTUMN BROWN

Product code : CARE P035 050

COMPANY : Increte Systems - A Division of The Euclid Chemical Company
 1611 Gunn Highway
 Odessa, FL 33556

Telephone : 1-800-752-4626

Emergency Phone: : U.S. only: 1-800-424-9300
 International Users Call Collect: 1-703-527-3887

SECTION 2 - HAZARDS IDENTIFICATION
Emergency Overview

Brown. Powder. May cause coughing and wheezing. Dust may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause coughing and wheezing. Dust may irritate respiratory tract.

Eyes : Dust may cause eye irritation. May cause mechanical irritation or abrasion. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	> 60.0
Pigment Yellow	20344-49-4	1.0 - 5.0
Iron oxide	1317-61-9	1.0 - 5.0
Iron oxide	1309-37-1	1.0 - 5.0
Calcium stearate	1592-23-0	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0



ANTIQUE RELEASE - 35# PL AUTUMN BROWN
ANTIQUE RELEASE - 35# PL
AUTUMN BROWN

Version 3.0

Print Date 04/25/2013

REVISION DATE: 07/08/2012

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings.
- Hazardous combustion products : Not available.
- Protective equipment for firefighters : Not applicable. Product is not expected to burn.
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions in sealed containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment



ANTIQUE RELEASE - 35# PL AUTUMN BROWN
ANTIQUE RELEASE - 35# PL AUTUMN BROWN

Version 3.0

Print Date 04/25/2013

REVISION DATE: 07/08/2012

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m3 15 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Iron oxide	1317-61-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Respirable particles. Inhalable particles. Total dust. Respirable fraction. Total dust. Respirable fraction.
Iron oxide	1309-37-1	OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA: ACGIH TWA:	10 mg/m3 15 mg/m3 5 mg/m3 5 mg/m3 5 mg/m3	Fume. Total dust. Respirable fraction. Respirable fraction. Respirable fraction.
Calcium stearate	1592-23-0	ACGIH TWA:	10 mg/m3	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Powder



ANTIQUUE RELEASE - 35# PL AUTUMN BROWN ANTIQUUE RELEASE - 35# PL AUTUMN BROWN

Version 3.0

Print Date 04/25/2013

REVISION DATE: 07/08/2012

Color	: Brown
Odor	: None
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Not available.
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Not available.
Specific Gravity	: 2.7023
% Volatile Weight	: 0.2 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Not Applicable.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:



ANTIQUUE RELEASE - 35# PL AUTUMN BROWN ANTIQUUE RELEASE - 35# PL AUTUMN BROWN

Version 3.0
 REVISION DATE: 07/08/2012

Print Date 04/25/2013

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
 Chronic Health Hazard

OSHA Hazardous Components :

Calcium Carbonate (Limestone)	1317-65-3
Iron oxide	1317-61-9
Iron oxide	1309-37-1
Calcium stearate	1592-23-0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

OSHA Status: Considered : Irritant
 hazardous based on the : Carcinogen
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l
 exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3
 Iron oxide 1309-37-1
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Penn RTK Components : Calcium Carbonate (Limestone) 1317-65-3
 Iron oxide 1309-37-1

NJ RTK Components : Calcium Carbonate (Limestone) 1317-65-3
 Pigment Yellow 20344-49-4



ANTIQUÉ RELEASE - 35# PL AUTUMN BROWN ANTIQUÉ RELEASE - 35# PL AUTUMN BROWN

Version 3.0

Print Date 04/25/2013

REVISION DATE: 07/08/2012

Iron oxide	1317-61-9
Iron oxide	1309-37-1
Calcium stearate	1592-23-0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System