

Date Prepared: 6/9/11
Supersedes: 1/13/05
Product Name: SureLock WB

ChemMasters

Safety Data Sheet

1. Chemical Product and Company Information

Product Name: SureLock WB

Product Description: High Solids, V.O.C. Compliant, Water based sealing compound.

ChemMasters
300 Edwards Street
Madison, Ohio 44057
440-428-2105

In Case of Emergency Contact:
CHEMTREC 800/424-9300

2. Hazards Identification

CAUTION

May Cause Eye Irritation

WHMIS Classification: Class D, Division 2B (Toxic)

Symbol: Stylized T

Potential Health Hazards - Acute

Eye: Direct contact may cause moderate irritation which may be slow to heal.

Skin: Prolonged or repeated exposure may cause slight irritation.

Inhalation: Exposure to mist may cause headache, nausea and/or other symptoms of upper respiratory tract irritation.

Ingestion: Slightly toxic. Large amounts may cause injury.

Potential Health Effects - Chronic:

None Known

Carcinogenicity:

NTP
NO

IARC Monographs
NO

OSHA Regulated
NO

3. Composition / Information on Ingredients

| Hazardous Components | CAS # | Exposure Limits | | OTHER |
|---|------------|-----------------|-----------------|-------|
| | | OSHA(PEL/TWA) | ACGIH (TLV/TWA) | |
| Water | 7732-18-5 | NE | NE | — |
| Acrylic Polymer, Proprietary | Non-Haz | NA | NA | — |
| Ethylene Glycol Monobutyl Ether | 111-76-2 | NE | NE | — |
| 2,2,4-trimethyl-1-3-pentandiol mono isobutyrate | 25265-77-4 | | NE | |

4. First Aid Measures

Eye: Immediately flush with plenty of water for 15 minutes.

Skin: Wash with soap and water.

Inhalation: Move victim to fresh air

Ingestion: If swallowed, give victim plenty of water. Consult a physician.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

Date Prepared: 6/9/11
Supersedes: 1/13/05
Product Name: SureLock WB

5. Fire Fighting Measures

Flash Point (method used): >200°F

Flammable Limits (% volume in air): Lower = No data available Upper = No data available

Auto Ignition Temperature: No data available

Extinguishing Media: Media appropriate for surrounding fire.

Hazard Combustion Products: Thermal decomposition may yield acrylic monomers, carbon monoxide and carbon dioxide.

Fire Fighting Instructions: Wear positive pressure, self-contained breathing apparatus.

6. Accidental Release Measures

Spill: Contain spilled material by diking. Absorb with inert material, then place in chemical waste container for later disposal. Keep spills out of municipal sewers and open bodies of water.

7. Handling and Storage

Handling: Always use good industrial hygiene practices and safety guidelines.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Protect from freezing.

8. Exposure Controls / Personal Protection

Exposure Controls: Mechanical exhaust is recommended for indoor use.

Personal Protection: Safety glasses and rubber gloves should be worn to minimize contact with this material. Use of a NIOSH approved vapor respirator is recommended when chance of mist exists. A source of clean water should be available in work area for flushing eyes and skin.

9. Physical and Chemical Properties

Appearance: Milky white liquid of water consistency

Odor: Acrylic odor

Boiling Point: 212°F

Melting Point: Not applicable

Vapor Pressure (mm/Hg): 17 @20°C

Vapor Density (Air = 1): <1.0

Solubility in Water: 100%

Specific Gravity (H₂O = 1): 1.01 (8.42 lb./gal)

Evaporation Rate (n-Butyl Acetate = 1): <1.0

10. Stability and Reactivity

Chemical Stability: Stable under normal conditions

Conditions to Avoid: Freezing and high temperatures

Incompatibility (materials to avoid): None

Hazardous Decomposition or By-products: May yield acrylic monomers, carbon monoxide and carbon dioxide

Hazardous Polymerization: Will not occur

Date Prepared: 6/9/11
Supersedes: 1/13/05
Product Name: SureLock WB

11. Toxicological Information

| Components | Oral LD50 (rat) | Dermal LD50 (rabbit) | Inhalation LC50 (rat) |
|---------------------------------|--------------------|-------------------------|--------------------------|
| Acrylic Polymer | > 5000 mg/kg | > 5000 mg/kg | > 5000 mg/kg |
| Ethylene Glycol Monobutyl Ether | 1,746 mg/kg | 435 mg/kg | |

12. Ecological Information

No data available

13. Disposal Considerations

Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for disposal.

This material does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however has not been evaluated by the Toxicity Characteristic Leaching procedure (TCLP).

14. Transportation Information

For U S National Shipments:

Shipping Description: Non-Regulated Material

Emergency Response Guide Number: Not applicable

Hazard Class: Not applicable

15. Regulatory Information

OSHA: This material is hazardous under the OSHA Hazard Communication Standard.

CERCLA Reportable Quantity: Not Applicable

SARA Title III:

Section 311/312 hazard categories: Acute health, delayed health

Section 313 reportable ingredients:

| Components | CAS # | Maximum % |
|---|----------|-----------|
| Ethylene Glycol Category (Glycol Ether EB) | 111-76-2 | 1.6 |

16. Other Information

MSDS Status: Revised 6/9/11

Industrial Abbreviation Legend on page 4 of this MSDS.

Date Prepared: 6/9/11
 Supersedes:1/13/05
 Product Name: SureLock WB

Industrial Abbreviation Legend

| | | | |
|--------|--|-------------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | mg/m ³ | milligrams per cubic meter |
| CAA | Clean Air Act (EPA) | NIOSH | National Institute for Occupational Safety and Health |
| CERCLA | Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund) (EPA) | NTP | National Toxicology Program |
| CNS | Central Nervous System | OSHA | Occupational Safety and Health Administration |
| CWA | Clean Water Act (EPA) | PEL | Permissible Exposure Limit |
| DOT | Department of Transportation | ppm | parts per million |
| EPA | Environmental Protection Agency | RCRA | Resource Conservation and Recovery Act (EPA) |
| g/kg | grams per kilogram | SARA | EPA's Superfund Amendment and Reauthorization Act (EPA) |
| IARC | Internal Agency for Research on Cancer | STEL | Short-Term Exposure Limit, ACGIH terminology |
| LC50 | Lethal Concentration in which 50% of the test animals are expected to die | TLV | Threshold Limit Value |
| LD50 | Lethal Dose in which 50% of the test animals are expected to die | TWA | Time-Weighted Average |

THIS PRODUCT IS FORMULATED AND LABELED FOR INDUSTRIAL AND COMMERCIAL APPLICATION ONLY

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The Spray-Cure Company assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.