

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01

Page: 1/11

Version: 2.0

(30605693/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No data available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	2	Flammable liquid
Skin Corr./Irrit.	2	Skin corrosion/irritation
Repr.	2 (unborn child)	Reproductive toxicity
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
STOT RE	2	Specific target organ toxicity — repeated

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 2/11
(30605693/SDS_GEN_US/EN)

Asp. Tox.	1	exposure
Aquatic Acute	2	Aspiration hazard
Aquatic Chronic	3	Hazardous to the aquatic environment - acute Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging the unborn child.
H373	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P271	Use only outdoors or in a well-ventilated area.
P243	Take precautionary measures against static discharge.
P273	Avoid release to the environment.
P260	Do not breathe dust/gas/mist/vapours.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P202	Do not handle until all safety precautions have been read and understood.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352	IF ON SKIN (on hair): Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.
P362 + P364	Take off contaminated clothing and wash before reuse.

Precautionary Statements (Storage):

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01

Page: 3/11

Version: 2.0

(30605693/SDS_GEN_US/EN)

P233 Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

WARNING:

FLAMMABLE LIQUID AND VAPOR.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Overexposure may cause CNS depression including headache, dizziness, nausea and loss of consciousness.

CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Contains a suspect teratogen.

Keep container tightly closed.

Avoid all sources of ignition: heat, sparks, open flame.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
108-88-3	>= 50.0 - < 75.0 %	Toluene
67-63-0	>= 5.0 - < 7.0 %	2-Propanol

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
108-88-3	>= 40.0 - <= 70.0 %	Toluene
14807-96-6	>= 7.0 - <= 13.0 %	talc
67-63-0	>= 3.0 - <= 7.0 %	2-Propanol
112945-52-5	>= 1.0 - <= 5.0 %	Silica
13463-67-7	>= 0.5 - <= 1.5 %	Titanium dioxide
1309-37-1	>= 0.5 - <= 1.5 %	Iron oxide

The product contains:

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14807-96-6	>= 7.0 - < 13.0 %	talc
57-50-1	>= 1.0 - < 3.0 %	Sucrose
1309-37-1	>= 0.5 - < 1.5 %	Iron oxide

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 4/11
(30605693/SDS_GEN_US/EN)

13463-67-7 >= 0.5 - < 1.5 % Titanium dioxide

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 5/11
(30605693/SDS_GEN_US/EN)

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and Storage

Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: tin (tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Sucrose	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ;
	ACGIH TLV	TWA value 10 mg/m3 ;
2-Propanol	OSHA PEL	PEL 400 ppm 980 mg/m3 ;
	ACGIH TLV	TWA value 200 ppm ; STEL value 400 ppm ;
Toluene	OSHA PEL	max. conc. 500 ppm ; CLV 300 ppm ; TWA value 200 ppm ;

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 6/11
(30605693/SDS_GEN_US/EN)

	ACGIH TLV	TWA value 20 ppm ;
Iron oxide	OSHA PEL ACGIH TLV	PEL 10 mg/m3 fumes/smoke ; TWA value 5 mg/m3 Respirable fraction ;
Titanium dioxide	OSHA PEL ACGIH TLV	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 ;
talc	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

Advice on system design:

No applicable information available.

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	solvent-like	
Odour threshold:		No applicable information available.
Colour:	pigmented	
pH value:		not applicable
Melting point:		No applicable information available.
Boiling point:	80 °C	
Sublimation temperature:		No applicable information available.
Flash point:	39 °F 4 °C	(ASTM D93)
Flammability:	Highly flammable.	

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 7/11
(30605693/SDS_GEN_US/EN)

Lower explosion limit:	1.2 %(V)	
Upper explosion limit:	12.7 %(V)	
Vapour pressure:		The product has not been tested.
Density:	0.96 - 1.15 g/cm ³	(20 °C)
Relative density:		No applicable information available.
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Viscosity, dynamic:		No applicable information available.
Viscosity, kinematic:		No applicable information available.
Solubility in water:		insoluble
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: No applicable information available.

Assessment other acute effects

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 8/11
(30605693/SDS_GEN_US/EN)

Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

Sensitization

Assessment of sensitization: No applicable information available.

Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Carcinogenicity

Assessment of carcinogenicity: The substance caused cancer in animal studies.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 9/11
(30605693/SDS_GEN_US/EN)

Information on: Toluene

Readily biodegradable (according to OECD criteria).

Additional information

Other ecotoxicological advice:
May cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Hazard class:	3
Packing group:	II
ID number:	UN 1139
Hazard label:	3
Proper shipping name:	COATING SOLUTION

Sea transport

IMDG

Hazard class:	3
Packing group:	II
ID number:	UN 1139
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	COATING SOLUTION

Air transport

IATA/ICAO

Hazard class:	3
Packing group:	II
ID number:	UN 1139
Hazard label:	3
Proper shipping name:	COATING SOLUTION

15. Regulatory Information

Federal Regulations

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01
Version: 2.0

Page: 10/11
(30605693/SDS_GEN_US/EN)

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic; Fire

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
1000 LBS	7727-43-7; 108-88-3	Barium sulfate; Toluene
100 LBS	67-63-0	2-Propanol

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	108-88-3	Toluene
MA, NJ, PA	14807-96-6	talc
MA, NJ, PA	67-63-0	2-Propanol
MA, PA	112945-52-5	Silica
MA, NJ, PA	13463-67-7	Titanium dioxide
MA, NJ, PA	1309-37-1	Iron oxide

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 2 Fire: 3 Reactivity: 0 Special:

HMIS III rating

Health: 2^a Flammability: 3 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2014/07/01

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE

Safety Data Sheet

MasterFinish HC 48 pnk also MBT HEATCOTE PINK

Revision date : 2014/07/01

Page: 11/11

Version: 2.0

(30605693/SDS_GEN_US/EN)

MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET