

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24

Page: 1/7

Version: 2.2

(30605694/SDS\_GEN\_CA/EN)

### 1. Product and Company Identification

Company

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

24 Hour Emergency Response Information

CANUTEC (reverse charges): (613) 996-6666  
BASF HOTLINE: (800) 454-COPE (2673)

### 2. Hazards Identification

Emergency overview

FLAMMABLE.  
IRRITANT.  
Irritating to eyes, respiratory system and skin.  
Contains a suspect teratogen.  
CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

State of matter: liquid  
Colour: pigmented  
Odour: solvent-like

Potential health effects**Acute toxicity:**

The product has not been tested. The statement has been derived from the properties of the individual components.

**Irritation / corrosion:**

Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Potential environmental effects**Aquatic toxicity:**

The product has not been tested.

### 3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Hazardous ingredients</u>
108-88-3	>= 40.0 - <= 70.0 %	Toluene
14807-96-6	>= 7.0 - <= 13.0 %	talc
67-63-0	>= 3.0 - <= 7.0 %	2-Propanol

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24

Page: 2/7

Version: 2.2

(30605694/SDS\_GEN\_CA/EN)

13463-67-7	>= 1.0 - <= 5.0 %	Titanium dioxide
112945-52-5	>= 1.0 - <= 5.0 %	Silica

---

### 4. First-Aid Measures

**General advice:**

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

**If inhaled:**

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

**If on skin:**

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

**If in eyes:**

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

**If swallowed:**

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

---

### 5. Fire-Fighting Measures

Flash point:	4 °C
Lower explosion limit:	1.2 %(V)
Upper explosion limit:	12.7 %(V)

**Suitable extinguishing media:**

foam, water spray, dry powder, carbon dioxide

**Unsuitable extinguishing media for safety reasons:**

water jet

**Hazards during fire-fighting:**

carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

**Protective equipment for fire-fighting:**

Wear a self-contained breathing apparatus.

**Further information:**

Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

### 6. Accidental release measures

**Personal precautions:**

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

**Environmental precautions:**

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24

Page: 3/7

Version: 2.2

(30605694/SDS\_GEN\_CA/EN)

### Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

## 7. Handling and Storage

### Handling

#### General advice:

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

#### Protection against fire and explosion:

Keep away from heat. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

### Storage

#### General advice:

Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight.

#### Storage incompatibility:

General advice: Segregate from metals. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

#### Temperature tolerance

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

## 8. Exposure Controls and Personal Protection

### Components with occupational exposure limits

2-Propanol	OSHA PEL	PEL 400 ppm 980 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 200 ppm ; STEL value 400 ppm ;
Titanium dioxide	ACGIH TLV	TWA value 10 mg/m <sup>3</sup> ;
talc	OSHA PEL	TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m <sup>3</sup> Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m <sup>3</sup> Total dust ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
	ACGIH TLV	TWA value 2 mg/m <sup>3</sup> Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24  
Version: 2.2

Page: 4/7  
(30605694/SDS\_GEN\_CA/EN)

### Personal protective equipment

#### **Respiratory protection:**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

#### **Hand protection:**

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

#### **Eye protection:**

Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

#### **General safety and hygiene measures:**

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

---

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	solvent-like	
Odour threshold:	No data available.	
Colour:	pigmented	
pH value:		not applicable
Boiling point:	80 °C	
Vapour pressure:		The product has not been tested.
Density:	approx. 1.0 g/cm3	( 20 °C)
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

---

## 10. Stability and Reactivity

#### **Substances to avoid:**

strong acids, strong bases, strong oxidizing agents

#### **Hazardous reactions:**

The product is stable if stored and handled as prescribed/indicated.

#### **Decomposition products:**

Thermal decomposition products: carbon oxides

#### **Oxidizing properties:**

Based on its structural properties the product is not classified as oxidizing.

---

## 11. Toxicological information

#### **Irritation / corrosion**

*Information on: Toluene*

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24  
Version: 2.2

Page: 5/7  
(30605694/SDS\_GEN\_CA/EN)

### Assessment of irritating effects:

*Skin contact causes irritation. May cause slight irritation to the eyes.*

### Information on: 2-Propanol

#### Assessment of irritating effects:

*Not irritating to the skin. Eye contact causes irritation.*

### Repeated dose toxicity

#### Information on: Toluene

#### Assessment of repeated dose toxicity:

*The substance may cause damage to the central nervous system after repeated ingestion of high doses. The substance may cause deafness after repeated inhalation.*

### Carcinogenicity

#### Information on: Titanium dioxide

*IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

#### Information on: talc

*In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed.*

### Development:

#### Information on: Toluene

*Indications of possible developmental toxicity/teratogenicity were seen in animal studies.*

### Aspiration Hazard:

May also damage the lung at swallowing (aspiration hazard).

### Experiences in humans:

According to experience, the product is considered to be harmless to health if used in the correct manner. Has degreasing effect on the skin.

### Other Information:

The product has not been tested. The statement has been derived from the properties of the individual components.

---

## 12. Ecological Information

### Other adverse effects:

Do not allow to enter soil, waterways or waste water channels.

---

## 13. Disposal considerations

### Waste disposal of substance:

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24  
Version: 2.2

Page: 6/7  
(30605694/SDS\_GEN\_CA/EN)

Do not discharge substance/product into sewer system. Dispose of in accordance with local authority regulations.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

## 14. Transport Information

### Land transport

TDG

Hazard class: 3  
Packing group: II  
ID number: UN 1139  
Hazard label: 3  
Proper shipping name: COATING SOLUTION

### Sea transport

IMDG

Hazard class: 3  
Packing group: II  
ID number: UN 1139  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: COATING SOLUTION

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: II  
ID number: UN 1139  
Hazard label: 3  
Proper shipping name: COATING SOLUTION

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

**WHMIS classification:** B2: Flammable Liquid

D2A: Materials Causing Other Toxic Effects - Very toxic material

D2B: Materials Causing Other Toxic Effects - Toxic material



**THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.**

# Safety Data Sheet

## MasterFinish HC 58 tan also MBT HEATCOTE TAN

Revision date : 2014/01/24

Page: 7/7

Version: 2.2

(30605694/SDS\_GEN\_CA/EN)

---

### 16. Other Information

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

**SDS Prepared by:**

BASF NA Product Regulations

BASF HOTLINE (800) 454 – COPE (2673)

SDS Prepared on: 2014/01/24

END OF DATA SHEET