



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 955-002P
Product name **Anti-Static Spray**
Effective date 10-Feb-2011
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 01

2. Hazards Identification

Emergency overview FLAMMABLE
Aerosol. CONTENTS UNDER PRESSURE.
Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Inhalation. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Liver. Lungs.

Chronic effects Liver injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Coughing. Liver enlargement. Jaundice. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Ethyl Alcohol	64-17-5	70 - 80
1,1-Difluoroethane	75-37-6	15 - 20
Non-hazardous and other components below reportable levels		0.1 - 1

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Skin contact Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops and persists.

Inhalation Move to fresh air. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician if symptoms develop or persist.

Ingestion

If material is ingested, immediately contact a poison control center. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media**Suitable extinguishing media**

Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Protection of firefighters**Protective equipment and precautions for firefighters**

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 2 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits**ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Ethyl Alcohol

64-17-5

1000 ppm

1000 ppm

Not established

OSHA**Components****CAS #****TWA****STEL****Ceiling**

Ethyl Alcohol

64-17-5

1000 ppm

Not established

Not established

Personal protective equipment**Eye / face protection**

Do not get in eyes. Chemical goggles are recommended.

Skin protection

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance

Compressed liquefied gas.

Boiling point	136.4 °F (57.8 °C) estimated
Color	clear colorless
Density	0.8114 g/cm3 estimated
Flammability (HOC)	21.0417 kJ/g estimated
Flash back	Yes
Flash point	-58 °F (-50 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	Characteristic.
pH	Not applicable
Physical state	Liquid.
Pressure	27 - 37 psig @70F
Solubility	Negligible
Specific gravity	0.8115

10. Chemical Stability & Reactivity Information

Chemical stability	Material is stable under normal conditions. Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LC50: 157 mg/l/4h estimated, Rat, Inhalation
Component analysis - LD50	
Toxicology Data - Selected LD50s and LC50s	
1,1-Difluoroethane	75-37-6 Inhalation LC50 Mouse 977 g/m3 2 h
Ethyl Alcohol	64-17-5 Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h
Sensitization	Not expected to be hazardous by OSHA criteria.
Carcinogenicity	
IARC - Group 1 (Carcinogenic to Humans)	
Ethyl Alcohol	64-17-5 Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [in preparation] (in alcoholic beverages)
Reproductive effects	Hazardous by OSHA criteria. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	Components of this product have been identified as having potential environmental concerns.
	LC50 16191 mg/L, Fish, 96.00 Hours, EC50 14503 mg/L, Daphnia, 48.00 Hours, IC50 , Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312)
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Ethyl Alcohol 64-17-5 Present

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 3
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Prepared by

Regulatory Compliance