



# SAFETY DATA SHEET

## 1. Identification

**Material name:** SUPER DIAMOND CLEAR 350 - 4/1 GAL  
**Material:** 359ADC 93

**Recommended use and restriction on use**

**Recommended use:** Coatings  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

EUCLID CHEMICAL COMPANY  
19218 REDWOOD ROAD  
CLEVELAND OH 44110  
US

**Contact person:** EH&S Department  
**Telephone:** 216-531-9222  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

**Hazard Classification**

**Physical Hazards**

Flammable liquids Category 2

**Health Hazards**

Skin Corrosion/Irritation Category 2  
Carcinogenicity Category 1B

**Unknown toxicity - Health**

Acute toxicity, oral 0.24 %  
Acute toxicity, dermal 0.25 %  
Acute toxicity, inhalation, vapor 99.95 %  
Acute toxicity, inhalation, dust or mist 100 %

**Environmental Hazards**

Acute hazards to the aquatic environment Category 2

**Unknown toxicity - Environment**

Acute hazards to the aquatic environment 92.87 %  
Chronic hazards to the aquatic environment 100 %

**Label Elements****Hazard Symbol:****Signal Word:**

Danger

**Hazard Statement:**Highly flammable liquid and vapor.  
Causes skin irritation.  
May cause cancer.  
Toxic to aquatic life.**Precautionary Statements****Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

**Response:**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Take off contaminated clothing. In case of fire: Use ... to extinguish.

**Storage:**

Store in well-ventilated place. Keep cool. Store locked up.

**Disposal:**

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Hazard(s) not otherwise classified (HNOC):**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**3. Composition/information on ingredients****Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
-------------------	------------	-------------------------



Aromatic petroleum distillates	64742-95-6	5 - <10%
1,2,4-Trimethylbenzene	95-63-6	1 - <5%
Diisodecyl phthalate	26761-40-0	1 - <5%
Cumene	98-82-8	0.1 - <1%
Xylene	1330-20-7	0.1 - <1%
Tert-Butyl Acetate	540-88-5	0.1 - <1%
Acetone	67-64-1	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

<b>Ingestion:</b>	Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
<b>Inhalation:</b>	Move to fresh air.
<b>Skin Contact:</b>	Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
<b>Eye contact:</b>	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

#### Most important symptoms/effects, acute and delayed

<b>Symptoms:</b>	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.
------------------	---

#### Indication of immediate medical attention and special treatment needed

<b>Treatment:</b>	Symptoms may be delayed.
-------------------	--------------------------

#### 5. Fire-fighting measures

<b>General Fire Hazards:</b>	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
------------------------------	--

#### Suitable (and unsuitable) extinguishing media

<b>Suitable extinguishing media:</b>	Use fire-extinguishing media appropriate for surrounding materials.
--------------------------------------	---

<b>Unsuitable extinguishing media:</b>	Avoid water in straight hose stream; will scatter and spread fire.
--	--

<b>Specific hazards arising from the chemical:</b>	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.
--	--

#### Special protective equipment and precautions for firefighters



**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

**Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

## 7. Handling and storage

**Precautions for safe handling:** Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling.

**Conditions for safe storage, including any incompatibilities:** Store locked up. Store in a well-ventilated place. Store in a cool place.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values		Source
Aromatic petroleum distillates	PEL	100 ppm	400 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m <sup>3</sup>	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	25 ppm	125 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	25 ppm	125 mg/m <sup>3</sup>	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)



	AN ESL	25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cumene	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	50 ppm 245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Tert-Butyl Acetate	TWA	50 ppm	US. ACGIH Threshold Limit Values (03 2016)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (03 2016)



	PEL	200 ppm 950 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Acetone	TWA	250 ppm	US. ACGIH Threshold Limit Values (03 2015)
	STEL	500 ppm	US. ACGIH Threshold Limit Values (03 2015)
	PEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Aromatic petroleum distillates	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Cumene	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm 246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

**Biological Limit Values**

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Acetone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEI (03 2015)

**Appropriate Engineering Controls**

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Individual protection measures, such as personal protective equipment****General information:**

Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

**Eye/face protection:**

Wear safety glasses with side shields (or goggles).

**Skin Protection****Hand Protection:**

Use suitable protective gloves if risk of skin contact.

**Other:**

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

**Respiratory Protection:**

In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

**Hygiene measures:**

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin.

**9. Physical and chemical properties****Appearance****Physical state:**

liquid

**Form:**

liquid

**Color:**

Colorless

**Odor:**

Mild petroleum/solvent

**Odor threshold:**

No data available.

**pH:**

No data available.



<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	> 35 °C > 95 °F
<b>Flash Point:</b>	17 °C 63 °F(Closed Cup)
<b>Evaporation rate:</b>	Slower than Ether
<b>Flammability (solid, gas):</b>	No
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.034
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Heat, sparks, flames.
<b>Incompatible Materials:</b>	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin. Causes skin irritation.
<b>Eye contact:</b>	Eye contact is possible and should be avoided.





**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

**Information on toxicological effects**

**Acute toxicity (list all possible routes of exposure)**

**Oral**

**Product:** ATEmix: 86,942.69 mg/kg

**Dermal**

**Product:** ATEmix: 2,768.87 mg/kg

**Inhalation**

**Product:** Not classified for acute toxicity based on available data.

**Specified substance(s):**

1,2,4-Trimethylbenzene LC 50 (Rat): 10,200 mg/m<sup>3</sup>

Diisodecyl phthalate LC 50 (Rat): > 12.54 mg/l

Acetone LC 50 (Rat): 76 mg/l

**Repeated dose toxicity**

**Product:** No data available.

**Skin Corrosion/Irritation**

**Product:** No data available.

**Specified substance(s):**



---

Aromatic petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
1,2,4-Trimethylbenzene	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Cumene	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Tert-Butyl Acetate	in vivo (Rabbit): Not irritant Experimental result, Key study
Acetone	in vivo (Rabbit): Not irritant Experimental result, Supporting study

**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Aromatic petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritating
Cumene	Rabbit, 24 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Tert-Butyl Acetate	Rabbit, 24 hrs: Not irritating
Acetone	Rabbit, 24 hrs: Minimum grade of severe eye irritant

**Respiratory or Skin Sensitization****Product:** No data available.**Carcinogenicity****Product:** May cause cancer. Suspected of causing cancer.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Cumene Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Cumene Reasonably Anticipated to be a Human Carcinogen.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**  
**Product:** No data available.

**In vivo**  
**Product:** No data available.

**Reproductive toxicity**  
**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**  
**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**  
**Product:** No data available.

**Aspiration Hazard**  
**Product:** No data available.

**Other effects:** No data available.

**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:****Fish**

**Product:** No data available.

**Specified substance(s):**

1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Cumene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Tert-Butyl Acetate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 296 - 362 mg/l Mortality



Acetone LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 5,490 - 7,030 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Diisodecyl phthalate EC 50 (Water flea (*Daphnia magna*), 48 h): > 0.02 mg/l Intoxication

Cumene LC 50 (Water flea (*Daphnia magna*), 48 h): 7.9 - 45.1 mg/l Mortality

Acetone LC 50 (Water flea (*Daphnia magna*), 24 h): 10 mg/l Mortality  
EC 50 (Water flea (*Daphnia magna*), 48 h): 21,600 - 23,900 mg/l Intoxication  
LC 50 (Scud (*Gammarus fasciatus*), 96 h): > 100 mg/l Mortality  
LC 50 (Asiatic clam (*Corbicula manilensis*), 96 h): > 20,000 mg/l Mortality  
LC 50 (Water flea (*Daphnia magna*), 96 h): > 100 mg/l Mortality

**Chronic hazards to the aquatic environment:****Fish**

**Product:** No data available.

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

**Persistence and Degradability****Biodegradation**

**Product:** No data available.

**BOD/COD Ratio**

**Product:** No data available.

**Bioaccumulative potential****Bioconcentration Factor (BCF)**

**Product:** No data available.

**Partition Coefficient n-octanol / water (log Kow)**

**Product:** No data available.

**Specified substance(s):**

Cumene Log Kow: 3.66

Xylene Log Kow: 3.12 - 3.20



Tert-Butyl Acetate            Log Kow: 1.76  
Acetone                        Log Kow: -0.24

**Mobility in soil:**                        No data available.  
**Other adverse effects:**                Toxic to aquatic organisms.

**13. Disposal considerations**

**Disposal instructions:**                Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.  
**Contaminated Packaging:**                No data available.

**14. Transport information**

**TDG:**  
UN1866, RESIN SOLUTION, 3, PG II  
**CFR / DOT:**  
UN1866, Resin solution, 3, PG II  
**IMDG:**  
UN1866, RESIN SOLUTION, 3, PG II

**Further Information:**  
The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**15. Regulatory information**

**US Federal Regulations**  
**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
None present or none present in regulated quantities.  
**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**  
None present or none present in regulated quantities.



**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Dimethyl carbonate	100 lbs.
Xylene	100 lbs.
Cumene	5000 lbs.
Tert-Butyl Acetate	5000 lbs.
Acetone	5000 lbs.
Methanol	5000 lbs.
Tert-Butyl Alcohol	100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Dimethyl carbonate	100 lbs.
Diisodecyl phthalate	
Xylene	100 lbs.
Cumene	5000 lbs.
Tert-Butyl Acetate	5000 lbs.
Acetone	5000 lbs.
Methanol	5000 lbs.
Tert-Butyl Alcohol	100 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Aromatic petroleum distillates	10000 lbs
1,2,4-Trimethylbenzene	10000 lbs
Diisodecyl phthalate	10000 lbs
Cumene	10000 lbs
Xylene	10000 lbs
Tert-Butyl Acetate	10000 lbs
Acetone	10000 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>
1,2,4-Trimethylbenzene

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

None present or none present in regulated quantities.

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.



## US State Regulations

### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Cumene	Carcinogenic. 09 2011
Methanol	Developmental toxin. 03 2012

### US. New Jersey Worker and Community Right-to-Know Act

#### Chemical Identity

Dimethyl carbonate  
Aromatic petroleum distillates  
1,2,4-Trimethylbenzene

### US. Massachusetts RTK - Substance List

#### Chemical Identity

Dimethyl carbonate  
Aromatic petroleum distillates  
1,2,4-Trimethylbenzene

### US. Pennsylvania RTK - Hazardous Substances

#### Chemical Identity

Dimethyl carbonate  
Aromatic petroleum distillates  
1,2,4-Trimethylbenzene  
Diisodecyl phthalate

### US. Rhode Island RTK

#### Chemical Identity

Aromatic petroleum distillates  
1,2,4-Trimethylbenzene

## International regulations

### Montreal protocol

not applicable

### Stockholm convention

not applicable

### Rotterdam convention

not applicable

### Kyoto protocol

not applicable

### VOC:

Regulatory VOC (less water and exempt solvent)	:	350 g/l
VOC Method 310	:	15.00 %

**Inventory Status:**

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

<b>Revision Date:</b>	02/28/2017
<b>Version #:</b>	7.0
<b>Further Information:</b>	No data available.





**Disclaimer:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.