

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- 7200, 7216, PREMIUM
STARTING FLUID -- 6850-00-823-7861

===== Product Identification =====

Product ID:7200, 7216, PREMIUM STARTING FLUID
MSDS Date:07/19/1989
FSC:6850
NIIN:00-823-7861
MSDS Number: CCLTD
=== Responsible Party ===
Company Name:VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.
Address:200 E MAIN ST
Box:14000
City:LEXINGTON
State:KY
ZIP:40512
Country:US
Info Phone Num:606-264-7000/7616;FAX 601-429-0537
Emergency Phone Num:800-ASHLAND/800-274-5263
CAGE:72527

=== Contractor Identification ===

Company Name:BALKAMP INC
Address:2601 S HOLT ROAD
Box:City:INDIANAPOLIS
State:IN
ZIP:46241
Country:US
Phone:317-244-7241
CAGE:70842
Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE
Address:ONE LINCOLN WAY
Box:City:ST. LOUIS
State:MO
ZIP:63120-1578
Country:US
Phone:414-255-5520
CAGE:050Q3
Company Name:VALVOLINE OIL CO
Address:3499 BLAZER PKY
Box:14000
City:LEXINGTON
State:KY
ZIP:40512
Country:US
Phone:606-357-7206 / 800-274-5263
CAGE:72527

===== Composition/Information on Ingredients =====

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 1-10%
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

Ingred Name:N-HEPTANE
CAS:142-82-5

RTECS #:MI7700000
 Fraction by Wt: 55-70%
 OSHA PEL:500 PPM/500 STEL
 ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:ETHYL ETHER (SARA III)
 CAS:60-29-7
 RTECS #:KI5775000
 Fraction by Wt: 25-40%
 OSHA PEL:400 PPM/500 STEL
 ACGIH TLV:400PPM/500STEL; 9192
 EPA Rpt Qty:100 LBS
 DOT Rpt Qty:100 LBS

Ingred Name:HEXANE (N-HEXANE)
 CAS:110-54-3
 RTECS #:MN9275000
 Fraction by Wt: 1-10%
 OSHA PEL:500 PPM
 ACGIH TLV:50 PPM; 9293
 EPA Rpt Qty:1 LB
 DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
 Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
 Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
 Health Hazards Acute and Chronic:PROLONGED &/OR REPEATED SKIN CONTACT
 MAY CAUSE IRRITATION, DEFATTING, DERMATITIS. EYE:MAY CAUSE SEVERE
 IRRITATION, REDNESS, TEARING, BLURRED VISION. SWALLOWING:MAY CAUSE
 G/I IRRITATION, NAUSEA, VOMITI NG, DIARRHEA. BREATHING:NASAL &
 RESPIRATORY IRRITATION, CNS EFFECTS.
 Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT
 CARCINOGENICITY. HMIS FOUND NO LISTING & DOES NOT EXPECT IT TO BE
 CARCINOGENIC.
 Effects of Overexposure:MFR GAVE NO INFORMATION OF MSDS. SEE HEALTH
 HAZARDS.
 Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION OF MSDS.

===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.
 EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE
 CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE. INHALED:REMOVE FROM
 EXPOSURE. A ID OR RESTORE BREATHING AS NEEDED. INGESTED:DO NOT
 INDUCE VOMITING. KEEP VICTIM WARM & QUIET & GET IMMEDIATE MEDICAL
 ATTENTION. ASPIRATION INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS -
 POSSIBLY FATAL.

===== Fire Fighting Measures =====

Flash Point Method:TCC
 Flash Point:<-50.C, -58.F
 Lower Limits:1
 Extinguishing Media:REGULAR FOAM OR CO2 OR DRY CHEMICAL.
 Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS
 COOL. WEAR SELF-CONTAINED BREATHING APPARATUS W/FULL FACEPIECE
 OPERATED IN POSITIVE PRESSURE MODE FOR FIGHTING FIRE
 Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR

NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL:ALLOW TO EVAPORATE. VENTILATE AREA. EMIMINATE IGNITION SOURCES. LARGE SPILL:ELIMINATE IGNITION SOURCES. EVACUATE UNPROTECTED PERSONNEL UNTIL LEAK IS REPAIRED.
Neutralizing Agent:MFR GAVE NO INFORMATION OF MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. OBSERVE WITH THEM ALL HAZARD PRECAUTIONS LISTED IN THIS DOCUMENT.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE LIMITS OF PRODUCT IS EXCEEDED WEAR A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS PERMIT OTHER RESPIRATORS UNDER SPECIFIED CONDITIONS.
Ventilation:USE MECHANICAL (GENERAL) VENTILATION & LOCAL EXHAUST TO KEEP EXPOSURE 1
Spec Gravity:<1
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:COMP GAS
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:MFR GAVE NO INFORMATION OF MSDS.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE & VARIOUS HYDROCARBONS, ETC.
Conditions to Avoid Polymerization:CANNOT OCCUR

===== Disposal Considerations =====

Waste Disposal Methods:SMALL SPILL:ALLOW MATERIAL TO EVAPORATE. LARGE SPILL:VENTILATE AREA OF SPILL. ALLOW MATERIAL TO EVAPORATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.